

§ 265.1050

40 CFR Ch. I (7–1–11 Edition)

§ 265.1050 Applicability.

(a) The regulations in this subpart apply to owners and operators of facilities that treat, store, or dispose of hazardous wastes (except as provided in § 265.1).

(b) Except as provided in § 265.1064(k), this subpart applies to equipment that contains or contacts hazardous wastes with organic concentrations of at least 10 percent by weight that are managed in one of the following:

(1) A unit that is subject to the permitting requirements of 40 CFR part 270, or

(2) A unit (including a hazardous waste recycling unit) that is not exempt from permitting under the provisions of 40 CFR 262.34(a) (i.e., a hazardous waste recycling unit that is not a 90-day tank or container) and that is located at a hazardous waste management facility otherwise subject to the permitting requirements of 40 CFR part 270, or

(3) A unit that is exempt from permitting under the provisions of 40 CFR 262.34(a) (i.e., a “90-day” tank or container) and is not a recycling unit under the provisions of 40 CFR 261.6.

(c) Each piece of equipment to which this subpart applies shall be marked in such a manner that it can be distinguished readily from other pieces of equipment.

(d) Equipment that is in vacuum service is excluded from the requirements of § 265.1052 to § 265.1060 if it is identified as required in § 265.1064(g)(5).

(e) Equipment that contains or contacts hazardous waste with an organic concentration of at least 10 percent by weight for less than 300 hours per calendar year is excluded from the requirements of §§ 265.1052 through 265.1060 of this subpart if it is identified, as required in § 265.1064(g)(6) of this subpart.

(f) The requirements of this subpart do not apply to the pharmaceutical manufacturing facility, commonly referred to as the Stonewall Plant, located at Route 340 South, Elkton, Virginia, provided that facility is operated in compliance with the requirements contained in a Clean Air Act permit issued pursuant to 40 CFR 52.2454. The requirements of this subpart shall apply to the facility upon termination

of the Clean Air Act permit issued pursuant to 40 CFR 52.2454.

(g) Purged coatings and solvents from surface coating operations subject to the national emission standards for hazardous air pollutants (NESHAP) for the surface coating of automobiles and light-duty trucks at 40 CFR part 63, subpart IIII, are not subject to the requirements of this subpart.

[NOTE: The requirements of §§ 265.1052 through 265.1064 apply to equipment associated with hazardous waste recycling units previously exempt under paragraph 261.6(c)(1). Other exemptions under §§ 261.4 and 265.1(c) are not affected by these requirements.]

[55 FR 25512, June 21, 1990, as amended at 61 FR 59970, Nov. 25, 1996; 62 FR 52642, Oct. 8, 1997; 62 FR 64661, Dec. 8, 1997; 69 FR 22661, Apr. 26, 2004]

§ 265.1051 Definitions.

As used in this subpart, all terms shall have the meaning given them in § 264.1031, the Act, and parts 260–266.

§ 265.1052 Standards: Pumps in light liquid service.

(a)(1) Each pump in light liquid service shall be monitored monthly to detect leaks by the methods specified in § 265.1063(b), except as provided in paragraphs (d), (e), and (f) of this section.

(2) Each pump in light liquid service shall be checked by visual inspection each calendar week for indications of liquids dripping from the pump seal.

(b)(1) If an instrument reading of 10,000 ppm or greater is measured, a leak is detected.

(2) If there are indications of liquids dripping from the pump seal, a leak is detected.

(c)(1) When a leak is detected, it shall be repaired as soon as practicable, but not later than 15 calendar days after it is detected, except as provided in § 265.1059.

(2) A first attempt at repair (e.g., tightening the packing gland) shall be made no later than 5 calendar days after each leak is detected.

(d) Each pump equipped with a dual mechanical seal system that includes a barrier fluid system is exempt from the requirements of paragraph (a), *provided* the following requirements are met: